

RCM-IPC215

RCM-IPC215

- 1. 1080P/720P/480P;
- 2. IR LED 100;
- 3. 100;
- 4. 100;
- 5. 100



RCM-IPC215

RCM-IPC215	
RCM-IPC215	
RCM-IPC215	DC12V/AC24 ±20%
RCM-IPC215	60W
RCM-IPC215	
RCM-IPC215	Pelco-P/D
RCM-IPC215	2400bps/4800bps/9600bps/19200bps
RCM-IPC215	1 255
RCM-IPC215	
RCM-IPC215	360°
RCM-IPC215	0.5° 220°

傾斜角	-90~+90° 水平角 180°
視野角	0.5°~200°/個
動作温度	
保存温度	機内 -40°C ~ 60°C 機外 0~50°C
湿度	0-95%
動作時間	
動作距離	監視距離 ≥ 80M
動作電圧	
動作電流	動作電流 HITACHI/SONY/SANYO/SAMSUNG/LG/CNB
動作電圧	2:1
動作電流	≥ 50dB
動作電流	PAL/NTSC
動作電流	
動作電流	
動作電流	
動作電流	
動作電流	
動作電流	

システム構成図



Richmor 锐驰
锐驰



Richmor

OEM & ODM Service

Brasil World Cup Supplier



Inner Training after study from Alibaba in July



Technical Training For Fast Response to Customer Richmor 锐驰



lecturer for Execution