

Richmor HD H.264 3G GPS Vehicle DVR rekordér MDR500SDG

- 1, Latest New H.264 Video Compression, G.726 Audio Code, 4CH Video & 2CH Audio.
- 2, Recording Mode Can be Option CIF/HD1/D1, Frame Quality Can be Adjusted.
- 3, Professional Power Design for Vehicle, 6~48V Wide Voltage; Over-load, Over-voltage, Short Circuit, Reverse Protection.
- 4, All Aviation Connectors, Super Stable, High Anti-shock, Easy installation plug in and out.
- 5, Support DC12V, DC5V Output, Can offer Power for Cameras and some Accessories.
- 6, 64GB SD Card Max with Data Redundary Tech, Ensuring Data Stable.
- 7, Auto Recording, Timing Recording, Alarm (Open/Close door) Recording Mode for Different Request.
- 8, Powerful file fragmentation removal technology and data protection features, support for abnormal restart protection function.
- 9, Special Delay Power off circuit, Which can support the system continuous running after vehicle power off.
- 10, 4CH Alarm vstuoní, Místní a Remote PTZ Control.
- 11, Support 3G, GPS, 3G Module: WCDMA/CDMA2000/TD-SCDMA..., Compatible with GPRS/EDGE;
- 12, Free software offered, Support Real-time Live videl, GPS Location, Scenshot, Playback, Analysis, Alarm, Log Management.
- 13, Support Upgrading through SD Card; support phone monitoring Android/IOS.



Popis

Položka	Parametr
& Amp; V & nbsp; vstup	4 & nbsp; kanál, & nbsp; letectví & nbsp; & nbsp; & nbsp; konektor
& Amp; V & nbsp; výstup	1 & nbsp; kanál, & nbsp; letectví & nbsp; & nbsp; & nbsp; konektor
Video & nbsp; komprese & H.264	
nbsp; formát	
Rozlišení	D1 / HD1 / CIF & nbsp; volitelná. D1, & nbsp; nejvyšší, & nbsp; CIF & nbsp; nejmenší
Video & nbsp; Rám & nbsp; nbsp; rychlost	100 & nbsp; fps & nbsp; (PAL), 120 fps (NTSC), 50fps (4 * D1)
Nahrávání	Fire & nbsp; nahrávání, & nbsp; čas & nbsp; nahrávání, & nbsp; alarm & nbsp; nahrávání
Skladování	Karta, SD & nbsp;
Alarm	1CH & nbsp; alarm; & nbsp; alarm & nbsp; a & nbsp; nahrávání & nbsp; na & nbsp; & nbsp; stejného & nbsp; čas
Vozidla & nbsp; nahrávání	Recording Vehicle operation (turn left/right, stop lamp), license NO., route, driver
System & nbsp; ochrana	Saving the recording data when the power off, support hard disk upgrading
Sif	RJ45 Ethernet interface and can copy the data through Wired/Wireless networks, controlling and managing the main machine.
PTZ & nbsp; kontrola	RS232 & nbsp; se & nbsp; otočit & nbsp; & nbsp; PTZ & nbsp; rozhraní
GPS	Support GPS module expansion, recoding and playback the vehicle route
G-SENSOR & nbsp; & nbsp; & nbsp; modul	Support G-Sensor module expansion, recording vehicle direction state and alarm
Baterie	Wide Voltage Range. Operation voltage: 6V~48V; Recommend range: 8V-40V; instantaneous range: 6-70V. Support overvoltage protection, under-voltage protection, short-circuit protection, transposition protection, fire on/off timing, delay power-off. Output voltage is 12v.
Prásek	2.4W
System	Embedded full-time multitask control system, support Chinese simplified & English
Pracovní & nbsp; životní prostředí	Working temperature: -20C°to 50C°, Working humidity: <90%; storage temperature: -30C to 70C, Storage humidity <90%
Rozměry	180mm * 145mm * 45mm

Příslušenství



AV Input Cables



AV Output Cable



Power Cable



IO Cables



Remote Control



GPS Antenna



CD (Manual & Software Inside)



SD Mobile DVR

Balení



Richmor Brand Package



Standard Package

Vlastní & Designed & Software & Screenshot



CE & FCC & ROHS & Certifikace



Přivítání a [Kontakt](#); Jenny na [podrobnosti](#)

E-mail: jenny@rcmccctv.com

Skype: [rcmccctvsales4](#)