

Richmor HD H.264 3G del veicolo DVR GPS MDR500SDG

- 1, Latest New H.264 Video Compression, G.726 Audio Code, 4CH Video & 2CH Audio.
- 2, Recording Mode Can be Option CIF/HD1/D1, Frame Quality Can be Adjusted.
- 3, Professional Power Design for Vehicle, 6~48V Wide Voltage; Over-load, Over-voltage, Short Circuit, Reverse Protection.
- 4, All Aviation Connectors, Super Stable, High Anti-shock, Easy installation plug in and out.
- 5, Support DC12V, DC5V Output, Can offer Power for Cameras and some Accessories.
- 6, 64GB SD Card Max with Data Redundary Tech, Ensuring Data Stable.
- 7, Auto Recording, Timing Recording, Alarm (Open/Close door) Recording Mode for Different Request.
- 8, Powerful file fragmentation removal technology and data protection features, support for abnormal restart protection function.
- 9, Special Delay Power off circuit, Which can support the system continuous running after vehicle power off.
- 10, 4CH & nbsp; Allarme & nbsp; Input, Local & nbsp; PTZ & nbsp;, e & nbsp; Remote & nbsp; controllo.
- 11, Support 3G, GPS, 3G Module: WCDMA/CDMA2000/TD-SCDMA..., Compatible with GPRS/EDGE;
- 12, Free software offered, Support Real-time Live video, GPS Location, Screenshot, Playback, Analysis, Alarm, Log Management.
- 13, Support Upgrading through SD Card; support phone monitoring Android/iOS.



Descrizione

Voce	Parametro
A & nbsp; V & nbsp; ingresso	4 & nbsp; canale, & nbsp; dell'aviazione & nbsp; & nbsp; & nbsp; & nbsp; connettore
A & nbsp; V & nbsp; uscita	1 & nbsp; canale, & nbsp; dell'aviazione & nbsp; & nbsp; & nbsp; & nbsp; connettore
Formato, Video & nbsp; compressione & nbsp;	H.264
Risoluzione	D1 / HD1 / CIF & nbsp; selezionabile D1-4l & nbsp; più alta, & nbsp; CIF-4l & nbsp; più basso
Video & nbsp; Frame & nbsp; tasso	100 & nbsp; fps & nbsp; (PAL), 120fps (NTSC), 50fps (4 * D1)
Registrazione	Fire & nbsp; registrazione, & nbsp; volta & nbsp; registrazione, & nbsp; allarme & nbsp; registrazione
Conservazione	SD & nbsp; carta
Allarme	1CH & nbsp; allarme; & nbsp; allarme & nbsp; e & nbsp; registrazione & nbsp; presso & nbsp; & nbsp; stesso & nbsp; il tempo
Veicolo & nbsp; registrazioni	Recording Vehicle operation (turn left/right, stop lamp), license NO., route, driver
System & nbsp; protezione	Saving the recording data when the power off, support hard disk upgrading
Rete	RJ45 Ethernet interface and can copy the data through Wired/Wireless networks, controlling and managing the main machine.
PTZ & nbsp; controllo	RS232 & nbsp; possono & nbsp; girare & nbsp; & nbsp; PTZ & nbsp; interfaccia
GPS	Support GPS module expansion, recoding and playback the vehicle route
G-SENSOR & nbsp; & nbsp; modulo	Support G-Sensor module expansion, recording vehicle direction state and alarm
Batteria	Wide Voltage Range, Operation voltage: 6V~48V; Recommend range: 8V-40V; instantaneous range: 6-70V. Support overvoltage protection, under-voltage protection, short-circuit protection, transposition protection, fire on/off timing, delay power-off. Output voltage is 12v.
Polvere	2.4W
Sistema	Embedded full-time multitask control system, support Chinese simplified & English
Lavoro & nbsp; ambiente	Working temperature: -20C°to 50C°; Working humidity: <90%; storage temperature: -30C to 70C, Storage humidity <90%
Dimensioni	180 millimetri * 145 millimetri * 45 millimetri

Accessori



AV Input Cables



AV Output Cable



Power Cable



IO Cables



Remote Control



GPS Antenna



CD (Manual & Software Inside)



SD Mobile DVR

Pacchetto



Richmor Brand Package



Standard Package

Own & Concezione & Software & Screenshot



CE & FCC & ROHS & Certificazione

