

Richmor HD H.264 3G GPS Veículo DVR Recorder MDR500SDG

- 1, Latest New H.264 Video Compression, G.726 Audio Code, 4CH Video & 2CH Audio.
- 2, Recording Mode Can be Option CIF/HD1/D1, Frame Quality Can be Adjusted.
- 3, Professional Power Design for Vehicle, 6~48V Wide Voltage; Over-load, Over-voltage, Short Circuit, Reverse Protection.
- 4, All Aviation Connectors, Super Stable, High Anti-shock, Easy installation plug in and out.
- 5, Support DC12V, DC5V Output, Can offer Power for Cameras and some Accessories.
- 6, 64GB SD Card Max with Data Redundary Tech, Ensuring Data Stable.
- 7, Auto Recording, Timing Recording, Alarm (Open/Close door) Recording Mode for Different Request.
- 8, Powerful file fragmentation removal technology and data protection features, support for abnormal restart protection function.
- 9, Special Delay Power off circuit, Which can support the system continuous running after vehicle power off.
- 10, 4CH Alarm Input, Local e remoto PTZ controle.
- 11, Support 3G, GPS, 3G Module: WCDMA/CDMA2000/TD-SCDMA..., Compatible with GPRS/EDGE;
- 12, Free software offered, Support Real-time Live video, GPS Location, Screenshot, Playback, Analysis, Alarm, Log Management.
- 13, Support Upgrading through SD Card; support phone monitoring Android/iOS.



Descrição

Item	Parâmetro
A & nbsp; V & nbsp; entrada	4 & nbsp; canal, & nbsp; aviação & nbsp; & nbsp; & nbsp; conector
A & nbsp; V & nbsp; saída	1 & nbsp; canal, & nbsp; aviação & nbsp; & nbsp; & nbsp; conector
Video & nbsp; compressão & nbsp; formato	H.264
Resolução	D1 / HD1 / CIF & nbsp; selecionável. D1-o & nbsp; mais alto, & nbsp; CIF-o & nbsp; menor
Video & nbsp; Frame & nbsp; taxa	100 & nbsp; fps & nbsp; (PAL), 120 fps (NTSC), 50fps (4 * D1)
Gravação	Fire & nbsp; gravação, & nbsp; tempo & nbsp; gravação, & nbsp; alarme & nbsp; gravação
Armazenamento	Cartão; SD & nbsp;
Alarme	1CH & nbsp; alarme; & nbsp; alarme & nbsp; e & nbsp; gravação & nbsp; AT & nbsp; & nbsp; mesma & nbsp; tempo
Veículo & nbsp; gravação	Recording Vehicle operation (turn left/right, stop lamp), license NO., route, driver
Sistema & nbsp; Proteção	Saving the recording data when the power off, support hard disk upgrading
Rede	RJ45 Ethernet interface and can copy the data through Wired/Wireless networks, controlling and managing the main machine.
PTZ & nbsp; controle	RS232 & nbsp; pode & nbsp; virar & nbsp; & nbsp; PTZ & nbsp; interface de
GPS	Support GFS module expansion, recoding and playback the vehicle route
G-SENSOR & nbsp; & nbsp; módulo	Support G-Sensor module expansion, recording vehicle direction state and alarm
Bateria	Wide Voltage Range. Operation voltage: 6V~48V; Recommend range: 8V-40V; instantaneous range: 6-70V. Support overvoltage protection, under-voltage protection, short-circuit protection, transposition protection, fire on/off timing, delay power-off. Output voltage is 12v.
Pó	2.4W
Sistema	Embedded full-time multitask control system, support Chinese simplified & English
Trabalho & nbsp; ambiente	Working temperature: -20C°to 50C°; Working humidity: <90%; storage temperature: -30C to 70C; Storage humidity <90%
Dimensões	180 milímetros * 145 milímetros * 45mm

Acessórios



AV Input Cables



AV Output Cable



Power Cable



IO Cables



Remote Control



GPS Antenna



CD (Manual & Software Inside)



SD Mobile DVR

Pacote



Richmor Brand Package



Standard Package

Próprio & Desenho & Software & tela



CE & FCC & ROHS & Certificação



Bem-vindo & nbsp; & nbsp; Contact & nbsp; Jenny & nbsp; por & nbsp; detalhes

**E-mail: jenny@rcmctv.com & nbsp; & nbsp; & nbsp; & nbsp; & nbsp; & nbsp;
Skype: [rcmctvsales4](https://www.skype.com/en/contacts/voice/rcmctvsales4)**